

Page 1 of 6 SDS-E-FN5S

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards SDS Revision Date: 8/3/2023 SDS Revision: 6.4 1. PRODUCT & COMPANY IDENTIFICATION 1 1 Product Name DEOXIT® FADER F-SERIES FN5, 5% SPRAY, NON-FLAMMABLE, VOC COMPLIANT 1.2 Chemical Name: 1.3 Synonyms DeoxIT® Fader F-Series 5% Spray; FN5S-6N and FN5S-2N (mini-spray) 1.4 Trade Names: DeoxIT® Fader F-Series 5% Spray; PN FN5S-6N (163 grams), PN FN5S-2N (40 grams) 1.5 Product Use: Lubricant for conductive plastics & carbon-based controls 1.6 Distributor's Name: CAIG Laboratories, Inc. 1.7 Distributor's Address: 12200 Thatcher Court, Poway, CA 92064-6876 USA 1.8 Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN205206) 1.9 Business Phone / Fax: +1 (800) 224-4123 2. HAZARDS IDENTIFICATION This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification 2 1 Hazard Identification: criteria of NOHSC: 1088 (2004) and ADG Code (Australia). WARNING! PRESSURIZED CONTAINER; MAY BURST IF HEATED. CAUSES EYE IRRITATION. Classification: Aerosols 3, Eye Irrit. 2B 2.2 Label Elements: Hazard Statements (H): H229 - Pressurized container; may burst if heated. H320 - Causes eye Precautionary Statements (P): P210 - Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. P251 - Do not pierce or burn, even after use. P264 - Wash thoroughly after handling. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy. Continue rinsing. P337+P313 - If eye irritation persist: Get medical advice/attention. P403 - Store in a well-ventilated place. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF) Other Warnings: KEEP OUT OF REACH OF CHILDREN. 3. COMPOSITION & INGREDIENT INFORMATION EXPOSURE LIMITS IN AIR (mg/m³) **ACGIH** NOHSC **OSHA** ppm ppm ppm ES-ES-ES-RTECS No. STFI CHEMICAL NAME(S) CAS No. **EINECS No.** TI V STEL TWA STEL **PEAK** PFI IDI H OTHER 102687-65-0 NA NA 60-100 NA NA NF NF NF NA NA NA SOLSTICE® PF REACH Reg. No. 01-2119855084-38 1-PROPENE, 1,3,3,3-29118-24-9 NA NA 15-30 NA NA NF NF NA NA NA NF TETRAFLUORO-, (1E) REACH Reg. No. 01-0000019758-54 NA NA NF NF NF 15 NA DEOXIT ® FADER F100L NA NA NA 3-7 NA (TRADE SECRET) REACH Reg. No. Non-hazardous/Proprietary 4. FIRST AID MEASURES If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk First Aid Ingestion: IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed Splashes are not likely; however, mist may cause irritation. If product gets in the eyes may cause irritation; Eyes: flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally. If irritation persists repeat flushing. Get medical attention. Skin: Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Treat for frostbite if necessary, be gently warming affected area. If irritation, redness or swelling persists, contact a physician immediately. Remove victim to fresh air at once. If breathing difficult, administer oxygen. Gross overexposure may Inhalation: cause central nervous system depression, dizziness, confusion, incoordination, drowsiness, irregular heartbeat accompanied by a strange feeling in the chest, "heart thumping," apprehension, lightheadedness, weakness, fainting, loss of consciousness, and death. 42 Effects of Exposure: Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and Eyes: watering. May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. Inhalation: Gross overexposure may cause central nervous system depression, dizziness, confusion, incoordination, drowsiness, irregular heartbeat accompanied by a strange feeling in the chest, "heart thumping,"

apprehension, light-headedness, weakness, fainting, loss of consciousness, and death.



Page 2 of 6 SDS-E-FN5S

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards SDS Revision: 6.4 SDS Revision Date: 8/3/2023

3	Symptoms of Overexposure:	Ingestion:	Nausea intes	stinal discomfor	t vomitin	a and/or d	cont'	<del>-</del>					
•	cymptome of overexpective.	Eyes:		e in eyes may o	-	•		aterina					
		Skin:		skin overexpo					nd irritatio	on of affe	ected a	reas Fi	roethi
		OKIT.		s. The produ									
		Inhalation:		posure may ca	ause cen	tral nervou	s system	depressi	on, dizzir	ness, cor	nfusion,	incoord	linatio
				irregular hear ı, light-headedr								eart thui	ımpin
ļ	Acute Health Effects:		ritation to eyes						n concer	ntrations	of vap	ors can	cau
	Chronic Health Effects		dizziness, head										
5	Chronic Health Effects:	respiratory h	re may trigger sypersensitivity.	Possible aller			nsitive in	dividuals.	May als	so induce	SKIN SE	ensitizati	ion a
i .	Target Organs:		Respiratory Sys										
,	Medical Conditions Aggravated by Exposure:		dermatitis, oth s (eyes, skin, a			disorders	of the	HEALT	Н				1
		larger organi	s (eyes, skiii, a	nd respiratory s	system).			FLAMN	<b>IABILIT</b>	Υ			1
								PHYSIC	CAL HA	ZARDS			0
								PROTE	CTIVE E	EQUIPM	IENT		В
								EYES	SKIN				
		. !					J					ı	
			5. F	IREFIGH1	TING N	<b>MEASU</b>	RES						
	Fire & Explosion Hazards:	Level 1 Aero	osol (NFPA 30E					ve 120 °F	Cool u	ninvolved	4		
	·		o prevent poss										
			e bursting, sta										
			involved in a										
		gases (e.g.,	CO, Hydrogen	Fluoride).									
2	Extinguishing Methods:	Water, Foam	n, CO <sub>2</sub> , Dry Che	emical. Use wa	ater spray	to cool un	opened o	ontainers					
										1 16			
3	Firefighting Procedures:	Fight fires a	as for surroun	ding materials	. As in	any fire,	wear M	SHA/NIOS	SH appro	oved self	- /		Λ
3	Firefighting Procedures:		as for surrounge										0
3	Firefighting Procedures:	contained br until well af	reathing appara ter the fire is	itus (pressure- out. Use wa	demand) ter spray	and full protocol fi	otective of	gear. Ke ed surfac	ep contai es and t	iners coo to protec	ol :t		0
3	Firefighting Procedures:	contained br until well af personal. F	reathing appara ter the fire is Fight fire upwin	ntus (pressure-out. Use war out. Use war nd. Avoid spra	demand) ter spray aying wat	and full pr to cool fi ter directly	otective ; re-expos into sto	gear. Ke ed surfac rage cont	ep contai es and t ainers be	iners coo to protec ecause o	ol et of		0
3	Firefighting Procedures:	contained br until well af personal. F danger of b	reathing appara iter the fire is Fight fire upwin poil-over. Prev	atus (pressure-out. Use wat out. Use wat d. Avoid spra rent runoff fror	demand) ter spray aying wat n fire co	and full protocol fi to cool fi ter directly ntrol or di	otective of re-exposi into sto lution fro	gear. Ke ed surfac rage cont m enterir	ep containes and the ainers being sewer	iners coo to protec ecause o s, drains	ol et of s,		0
3	Firefighting Procedures:	contained br until well af personal. F danger of b drinking wat	reathing appara fter the fire is Fight fire upwin poil-over. Prev fer supply, or a	atus (pressure- out. Use wat d. Avoid spra ent runoff fror ny natural wat	demand) ter spray aying wat n fire co erway. F	and full protocolor to cool fi ter directly ntrol or di Firefighters	otective gre-expose into sto lution from must us	gear. Ke ed surfac rage cont m enterir e full bun	ep containes and the same of a sewer	iners coo to protec ecause o s, drains includino	ol et of s,		0
3	Firefighting Procedures:	contained br until well af personal. F danger of b drinking wat NIOSH-appr	reathing appara fter the fire is Fight fire upwin ooil-over. Prev er supply, or a roved positive p	atus (pressure- out. Use wat d. Avoid spra ent runoff fror ny natural wat pressure self-co	demand) ter spray aying wat n fire co erway. F ontained	and full protection to cool fitter directly ntrol or differentiations are the cooler to the cooler t	otective gre-expose into sto lution from must us apparatus	gear. Ke ed surfac rage cont m enterir e full bun s to protec	ep containes and the same of a sewer	iners coo to protec ecause o s, drains includino	ol et of s,		0
3	Firefighting Procedures:	contained br until well af personal. F danger of b drinking wat NIOSH-appr	reathing appara fter the fire is Fight fire upwin poil-over. Prev fer supply, or a	atus (pressure- out. Use wat d. Avoid spra ent runoff fror ny natural wat pressure self-co	demand) ter spray aying wat n fire co erway. F ontained	and full protection to cool fitter directly ntrol or differentiations are the cooler to the cooler t	otective gre-expose into sto lution from must us apparatus	gear. Ke ed surfac rage cont m enterir e full bun s to protec	ep containes and the same of a sewer	iners coo to protec ecause o s, drains includino	ol et of s,		0
3	Firefighting Procedures:	contained br until well af personal. F danger of b drinking wat NIOSH-appr hazardous c	reathing appara fter the fire is Fight fire upwin ooil-over. Prev er supply, or a roved positive p	atus (pressure- out. Use wai id. Avoid spra- rent runoff fror ny natural wat pressure self-co ecomposition p	demand) ter spray aying wat m fire co erway. F pontained	and full promote to cool fitter directly introl or different firefighters breathing and oxygen	otective gre-exposion into sto lution from must us apparatus deficien	gear. Ke ed surfac rage cont m enterir e full bun s to protec cies.	ep containes and the same of a sewer	iners coo to protec ecause o s, drains includino	ol et of s,		<u>0</u>
	Firefighting Procedures:  Spills:	contained br until well af personal. F danger of b drinking wat NIOSH-appr hazardous c	reathing appara- fer the fire is Fight fire upwin coil-over. Prev- er supply, or a roved positive p combustion or d	atus (pressure-tout. Use waited. Avoid spratent runoff from ny natural wateressure self-coecomposition p	demand) ter spray aying waf in fire co erway. F ontained l iroducts a	and full pr to cool fi ter directly ntrol or di Firefighters breathing a and oxygen	re-exposinto sto lution from must us apparatus deficien	gear. Ke ed surfac rage cont m enterir e full bun s to protec cies.	ep conta es and t ainers be ig sewer ker gear tt against	iners coo to protec ecause o es, drains includino t potentia	ol et of s, g	onal Pro	otecti
		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c	reathing apparater the fire is Fight fire upwin poil-over. Previer supply, or a coved positive pombustion or d.	atus (pressure-tout. Use waited. Avoid spratent runoff from ny natural water self-composition position	demand) ter spray aying wat in fire co erway. If ontained l products a  RELEA duals inv	and full protocool fiter directly ntrol or discretishing and oxygen  ASE ME volved in s	re-expose into sto lution from must us apparatus deficien  EASUI	gear. Ke ed surfac rage cont m enterir e full bun s to protec cies.  RES nup must	ep contai es and tainers being sewer ker gear et against	iners coo to protec ecause o s, drains including t potentia	e Perso		
		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c	reathing apparater the fire is Fight fire upwin poil-over. Prever supply, or a coved positive pombustion or defeated.  6. ACCIL aning any spill	atus (pressure-tout. Use waited. Avoid spratent runoff from ny natural water ecomposition position pos	demand) ter spray aying wat in fire co erway. If contained l roducts a  RELEA duals involver, ey	and full protocool fiter directly ntrol or discretifications of the cool fiter directly ntrol or discretifications of the cool full protocool	otective of re-expose into sto lution from must us apparatus deficien  EASUI  spill clea on and ap	gear. Ke ed surface rage cont m enterir e full bun s to protect cies.  RES nup must ron may b	ep contai es and tainers being sewer ker gear et against	iners coo to protect ecause of s, drains including t potentia	e Perso	f large s	pills.
		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c  Before clea Equipment. Small Spills	reathing apparater the fire is Fight fire upwin poil-over. Prever supply, or a coved positive pombustion or defect the combustion or defect aning any spill Plastic or rubi	atus (pressure-tout. Use waited. Avoid spratent runoff from ny natural water sesure self-coecomposition position positio	demand) ter spray aying wat m fire co erway. Fontained products a  RELEA duals involuter, ey equipme	and full protocool fiter directly ntrol or differentiates breathing and oxygen  ASE ME  volved in seve protection including	re-exposinto sto lution fromust us apparatus deficien  EASUI spill clean and apg gloves	gear. Ke ed surface rage cont m enterir e full bun s to protect cies.  RES nup must ron may b and protect	ep contai es and tainers beig sewer ker gear et against wear ag e require ective eye	iners coo to protect ecause o s, drains including t potentia  ppropriate ed for clea	e Perso	f large s on-comb	pills. oustik
		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c  Before clea Equipment. Small Spills material suc	reathing apparater the fire is fight fire upwin poil-over. Previer supply, or a coved positive pombustion or defect the first and any spill plastic or rubit. Wear appropriate the first supplemental than the first supplemental	atus (pressure-cout. Use waited. Avoid spratent runoff from ny natural water sesure self-corecomposition popular processors, individual protective are or sand to set the second service of the second second service of the second	demand) ter spray aying wat m fire co erway. Fortained products a  RELEA  duals involution, ey equipme oak up the	and full protocool fiter directly ntrol or differentiates breathing and oxygen  ASE ME  Volved in seve protection including the product	re-exposinto sto lution from must us apparatus deficien  EASUI  spill clea an and ap g gloves and place an	gear. Ke ed surface rage cont m enterir ee full bun es to protecties.  RES nup must and protecties and protecti	ep containers and it ainers being sewer ker gear at against wear at the requirement of the container in the	iners coo to protect ecause o s, drains including t potentia  ppropriate ed for clea ewear. U for later	e Persoan-up of disposa	f large s on-comb al. Do r	spills. oustik not u
		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c  Before clea Equipment. Small Spills material suc water or a r	reathing apparater the fire is fight fire upwin poil-over. Previer supply, or a roved positive prombustion or defection and supply supply the s	atus (pressure-cout. Use waid. Avoid spraient runoff from ny natural water sesure self-corecomposition popular protective in the protective is or sand to see seed of the protective is seed of the prot	demand) ter spray aying waf m fire co erway. Fortained products a  RELEA  duals involvator, ey equipme oak up the	and full protection to cool fitter directly introl or differentiates breathing and oxygen  ASE ME  Volved in seve protection tincluding the product up material	otective gre-exposition into sto lution from must us apparatus deficien  EASUI spill clea an and ap g gloves and place and lace a	gear. Ke ed surface rage cont m enterir ee full bun es to protecties.  RES nup must and protecties and protecties acception of the control of	ep containers and it ainers being sewer ker gear at against wear at the requirement of the container erial usin.	iners coo to protect ecause o s, drains including t potentia  ppropriate ed for clea ewear. U for later g non-sp	e Persoan-up of disposalarking i	f large s on-comb al. Do r materials	spills. oustik not u
		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c  Before clea Equipment. Small Spills water or a r plastic broor Large Spills	reathing apparater the fire is fire the fire is fire upwin tool-over. Prever supply, or a roved positive prombustion or defended in the first paragraph of the f	atus (pressure-tout. Use waited. Avoid spraent runoff from any natural water spraessure self-corecomposition position po	demand) ter spray aying wat in fire co erway. If products a  RELEA duals involution involution, ey equipme oak up th to soak ace into a s (e.g., or	and full protocool fiter directly introl or differential from the cool fiter directly introl or differential from the cool for the cool from t	re-exposition from the first state of the first sta	gear. Ke ed surface rage cont mentering e full bund is to protect cities.  RES  nup must ron may be and protect einto a ce p up mate plastic lir away fror	ep conta es and tainers be g sewer ker gear et against wear ap ee require container erial usin ner within n spill. S	iners coo to protect ecause o s, drains including t potentia  popropriate ed for clea ewear. U for later g non-sp another	e Perso an-up of disposa arking i	f large s on-comb al. Do r materials er. away fro	spills. oustib not u ls (e.
		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c  Before clea Equipment. Small Spills material suc water or a r plastic broor Large Spills or release.	reathing apparater the fire is fire the fire is fire upwin tool-over. Prevent supply, or a roved positive prombustion or defended in the first paragraph of the	atus (pressure-rout. Use waited. Avoid spracent runoff from any natural waterssure self-coecomposition popular protective or sand to see "speedy dry" stpans) and platible materials ate hazard area	demand) ter spray aying wat m fire co erway. I products a  RELEA  duals inv pirator, ey equipme oak up th to soak ace into a s (e.g., or a and kee	and full protection to cool fitter directly introl or differential formation of the cool o	re-exposition from the state of	gear. Ke ed surface rage cont mentering e full bund is to protect cies.  RES nup must ron may be and protect ep up mate plastic lir away fron sonnel out	ep conta es and tainers be g sewer ker gear et against wear ap ee require container erial usin her within n spill. S of area.	iners coo to protect ecause o s, drains including t potentia popropriate ed for clea ewear. U for later g non-sp another Stop spi	e Perso an-up of disposa arking i containe	f large s on-comb al. Do r materials er. away fro ease if it	spills. oustik not u ls (e. om s t can
		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c  Before clea Equipment. Small Spills material suc water or a r plastic broor Large Spills or release.	reathing apparater the fire is fire the fire is fire upwin tool-over. Prever supply, or a roved positive prombustion or defended in the first paragraph of the f	atus (pressure-rout. Use waited. Avoid spracent runoff from any natural waterssure self-coecomposition popular protective or sand to see "speedy dry" stpans) and platible materials ate hazard area	demand) ter spray aying wat m fire co erway. I products a  RELEA  duals inv pirator, ey equipme oak up th to soak ace into a s (e.g., or a and kee	and full protection to cool filter directly introl or differential filter and oxygen and oxygen and oxygen and oxygen are protection in the product up material plastic conganics such punauthol	re-exposition from the state of	gear. Ke ed surface rage cont mentering e full bund is to protect cies.  RES nup must ron may be and protect ep up mate plastic lir away fron sonnel out	ep conta es and tainers be g sewer ker gear et against wear ap ee require container erial usin her within n spill. S of area.	iners coo to protect ecause o s, drains including t potentia popropriate ed for clea ewear. U for later g non-sp another Stop spi	e Perso an-up of disposa arking i containe	f large s on-comb al. Do r materials er. away fro ease if it	spills. oustik not u ls (e. om s t can
		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous compared by the second	reathing apparater the fire is fire the fire is fire upwin tool-over. Prevent supply, or a roved positive prombustion or defended in the first such as vermiculity that is the first such as the	atus (pressure- out. Use wai d. Avoid spra ent runoff fror ny natural wat pressure self-co ecomposition p  DENTAL F  or leak, indivi per gloves, ries eig or sand to s s "speedy dry" stpans) and pla atible materials ate hazard area ear appropriate	demand) ter spray aying wat m fire co erway. I products a  RELEA  duals involutator, ey equipme oak up the to soak ace into a s (e.g., or a and kee protective	and full protocool fiter directly introl or differential formation of the cool	re-exposinto sto dution from the storic deficien from the storic deficient fr	gear. Ke ed surface rage cont mentering e full bund is to protect cies.  RES  nup must ron may be and protect ee into a ce p up mate plastic lir away from sonnel out ng respira	ep conta es and tainers be g sewer ker gear et against wear ap ee require container erial usin her within n spill. S of area.	iners coo to protect ecause o s, drains including t potentia popropriate ed for clea ewear. U for later g non-sp another Stop spi	e Perso an-up of disposa arking i containe	f large s on-comb al. Do r materials er. away fro ease if it	spills. oustib not us ls (e.ç om s t can
1	Spills:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous compared by the second	reathing apparater the fire is fire the fire is fire upwin poil-over. Prever supply, or a roved positive pombustion or defect the first point of t	atus (pressure- out. Use wai d. Avoid spra ent runoff fror ny natural wat pressure self-co ecomposition p  DENTAL F  or leak, indivi per gloves, resprate protective ter or sand to s s "speedy dry" estpans) and pla patible materials ate hazard area ear appropriate	demand) ter spray aying waf m fire co erway. F ontained droducts a  RELEA duals involvirator, ey equipme oak up th to soak ace into a s (e.g., or a and kee protective	and full protocool fiter directly ntrol or discretified and oxygen  ASE ME  volved in some product up material plastic conganics such production e equipment	re-exposinto stolution fromust us apparatus deficien  EASUI spill clean and apg gloves and place and place and includication or the spill clean trainer of the spill clean and apg gloves and place and includication of the spill clean trainer of the spill clean trai	gear. Ke ed surface rage cont m enterir e full bun e to protecties.  RES  nup must ron may be and protecte into a co p up mate p up mate r plastic lir away fror connel out ng respira	ep conta es and tainers be g sewer ker gear et against wear ap e require ctive eye container erial usin ner within n spill. S of area.	iners coo to protect ecause of s, drains including t potential oppropriate ed for clea ewear. Uf for later g non-sp another Stay upwing Stop spi ection as	e Perso an-up of Jse a no disposa arking i containe nd and ill or rele conditio	f large s on-comb al. Do r materials er. away fro ease if it ons warr	spills. coustible not us ls (e.g) om s t can rant.
1		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous compared by the second	reathing apparater the fire is fire the fire is fire upwin look over. Prever supply, or a roved positive prombustion or defending any spill plastic or ruble. Wear approprict as vermiculif material such a ms, shovels, due Keep incomp Isolate immedianimal risk. Wear makerial such a ms, shovels, due Keep incomp Isolate immedianimal risk. Wear makerial such a ms, shovels, due Keep incomp Isolate immedianimal risk. Wear makerial such a ms, shovels, due Keep incomp Isolate immedianimal risk. Wear makerial such a ms, shovels, due Keep incomp Isolate immedianimal risk. Wear ms, shovels, due immedianimal risk. Wear ms, shovels, due immedianimal risk. Wear ms, shovels, due immedianimal risk was makerial such a ms, shovels, due immedianimal risk was makerial such a ms, shovels, due immedianimal risk was makerial such a ms, shovels, due immedianimal risk was makerial such a ms, shovels, due immedianimal risk was makerial such a ms, shovels, due immedianimal risk was ms, shovels, due immedia	atus (pressure-tout. Use waited. Avoid sprayer trunoff from pressure self-corecomposition properties or leak, individually in the protective are or sand to see suppose the self-corecomposition protective are or sand to see suppose to self-corecomposition protective are or sand to see suppose the self-corecomposition protective are and protective are appropriate are appropriate.	demand) ter spray aying waf in fire co erway. If products a  RELEA duals involutes a equipme oak up the to soak ace into a s (e.g., or a and kee protective  ORAC  ng this p	and full protocool fiter directly introl or differential formation of the first separate	re-exposition for must us apparatus deficien  EASUI  spill clea and apg gloves and placal. Sweeth tainer out as oil) fized persont includi	gear. Ke ed surface rage cont mentering e full bun is to protect cies.  RES nup must ron may be and protect ee into a ce p up mate plastic lir away from sonnel out ng respira  TION under pre	ep contales and tainers beg sewer ker gear at against wear appeared to the container erial using the container within an spill. Sof area. tory protesssure.	iners coo to protect ecause o s, drains including t potentia  ppropriate ed for clea ewear. U for later g non-sp another Stay upwin Stop spi ection as	e Personal de la condition de	f large sion-comb al. Do r materials er. away fro ease if it ons warr	spills. coustible not u s (e.graph com s t can rant.
	Spills:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous compared by the second	reathing apparater the fire is fire the fire is fire upwin poil-over. Prever supply, or a roved positive pombustion or defect the first point of t	atus (pressure-tout. Use waited. Avoid spraent runoff from any natural water spraent runoff from a spraessure self-corecomposition probently of the self-core self-core gloves, respirate protective are or sand to see successive spraent of the self-core self	demand) ter spray aying waf in fire co erway. If products a  RELEA duals invo pirator, ey equipme oak up the to soak ace into a s (e.g., or a and kee protective  ORAC  ng this p o additior	and full protection to cool filter directly introl or differential protection.  ASE ME volved in some protection of the product of the product of the product of the product of the product. Contain protection of the product. Contain protection of the product. Contain protection of the product of the product. Contain protection of the p	re-exposition store into store dution from the store must us apparatus deficien  EASUI spill clea on and app gloves and place and place into the store of the sto	gear. Ke ed surface rage cont mentering e full bun is to protect cies.  RES nup must ron may be and protect einto a ce p up mate plastic lir away fror sonnel out ng respira  TION under pre ment is no	ep contales and tainers beg sewer ker gear at against wear appeared to the container erial using the container within an spill. Sof area. tory protesssure.	iners coo to protect ecause o s, drains including t potentia  ppropriate ed for clea ewear. U for later g non-sp another Stay upwin Stop spi ection as	e Personal de la condition de	f large sion-comb al. Do r materials er. away fro ease if it ons warr	spills. coustible not us ls (e.graph com s t can rant.
1	Spills:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous compared by the second	reathing apparater the fire is fire the fire is fire upwin look over. Prever supply, or a roved positive prombustion or defended in the first of the supply of the first over the first ov	atus (pressure-tout. Use waited. Avoid spraent runoff from any natural water spraent runoff from a spraent runoff from poetal, individual protective are or sand to see "speedy dry" astpans) and plantible materials at hazard area appropriate  ING & ST  e when handling intended, not unintentional re	demand) ter spray aying waf in fire co erway. If products a  RELEA  duals involutes a  cup equipme oak up the to soak ace into a ace into a ace protective  ORAC  ng this p additior sidues wi	and full protectly ntrol or differential full protection of the control of the co	re-exposition store into store dution from the store into store in	gear. Ke ed surface rage cont mentering e full bun is to protect cies.  RES nup must ron may be and protect einto a ce p up mate plastic lir away fror sonnel out ng respira  TION under pre ment is ne vater.	ep contales and tainers being sewer ker gear et against wear appeared to again the against wear against	iners coo to protect ecause o s, drains including t potentia  popropriate ed for clea ewear. U for later g non-sp another Stop spi ection as  Handle a	e Personal disposa arking in condition as to available as to a	f large sign-combal. Do rimaterials er. away froasse if it ons warra	spills. coustible not us ls (e.go com s t can rant. ncturi s if e
1	Spills:  Work & Hygiene Practices:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous compared by the second	reathing apparater the fire is fire the fire is fire upwin tool-over. Prevent supply, or a roved positive prombustion or defended in the first such as vermiculity material such a ms, shovels, due Keep incomplisolate immedianimal risk. We consider the first such as sessible. Wash to the first such a ms, shovels, due Keep incomplisolate immedianimal risk. We consider the first such a ms, shovels, due Keep incomplisolate immedianimal risk. We consider the first such as the first	atus (pressure-tout. Use waited. Avoid spraent runoff from any natural water spraent runoff from a spraent runoff from poetal, individual protective are or sand to see successive and plantible materials at a hazard area are appropriate.  ING & ST.  e when handlift as intended, not an intended and intended	demand) ter spray aying waf in fire co erway. If broducts a  RELEA  duals involutes a  cup equipme oak up the to soak ace into a s (e.g., or a and kee protective  ORAC  ng this p o addition sidues wi ted locat	and full protectly ntrol or differential protectly ntrol or differential protectly and oxygen  ASE ME  Volved in seven protection product conganics such product conganics such product. Considered product. Considered protection product. Considered protection of the protection of the product considered protection of the protection of th	re-exposition store into store in	gear. Ke ed surface rage cont mentering e full bund is to protect cies.  RES nup must ron may be and protect einto a ce p up mate plastic lir away fror sonnel out ng respira  TION under pre ment is ne water. aust venti	ep contales and tainers being sewer ker gear et against wear apperent eye container erial using a specific series within a spill. So farea, tory protes exessure.	iners coo to protect ecause o s, drains including t potentia  popropriate ed for clea ewear. U for later g non-sp another Stop spi ection as  Handle a . Use ch	e Personal de Pers	f large sign-combal. Do rimaterials er. away froase if it ons warring goggles heat and	spills. coustible not us ls (e.g) com s t can rant. neturi s if e
1	Spills:  Work & Hygiene Practices:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous compared by the second second by the second	reathing apparater the fire is fire the fire is fire upwin look over. Prever supply, or a roved positive prombustion or defended in the first of the supply of the first over the first ov	atus (pressure- out. Use wai d. Avoid spra ent runoff fror ny natural wat ressure self-co ecomposition p  DENTAL F  or leak, indivi per gloves, reisy riate protective et or sand to s s "speedy dry" stpans) and pla ratible materials ate hazard area ear appropriate  ING & ST  e when handli as intended, no unintentional re liry, well-ventilal es above 120°	demand) ter spray aying waf m fire co erway. I products a  RELEA  duals involuted involutes a  quipme oak up the to soak ace into a s (e.g., or a and kee protective  ORAG  ng this p o addition sidues wi ted locat F. Keep	and full protection to cool fiter directly introl or differential and oxygen and oxygen and oxygen and oxygen and oxygen are protection in a plastic conganics such a plastic conganics such a plastic conganics such and protection (e.g., I away from	re-exposition store into store in	gear. Ke ed surface rage cont mentering e full bund is to protect cies.  RES nup must ron may be and protect ee into a ce p up mate plastic lir away fror sonnel out ng respira  TION under pre ment is ne water. aust venti	ep contales and tainers being sewer ker gear et against wear apperent eye container erial using a specific series within a spill. So farea, tory protes exessure.	iners coo to protect ecause o s, drains including t potentia  popropriate ed for clea ewear. U for later g non-sp another Stop spi ection as  Handle a . Use ch	e Personal de Pers	f large sign-combal. Do rimaterials er. away froase if it ons warring goggles heat and	spills. coustible not us ls (e.g) com s t can rant. neturi s if e
•	Spills:  Work & Hygiene Practices:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous compared by the second second by the second	reathing apparater the fire is fire the fire is fire upwin tool-over. Prevent supply, or a roved positive prombustion or defended in the fire is the fire in a cool, or or in a cool, or or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is t	atus (pressure- out. Use wai d. Avoid spra ent runoff fror ny natural wat ressure self-co ecomposition p  DENTAL F  or leak, indivi per gloves, reisy riate protective et or sand to s s "speedy dry" stpans) and pla ratible materials ate hazard area ear appropriate  ING & ST  e when handli as intended, no unintentional re liry, well-ventilal es above 120°	demand) ter spray aying waf m fire co erway. I products a  RELEA  duals involuted involutes a  quipme oak up the to soak ace into a s (e.g., or a and kee protective  ORAG  ng this p o addition sidues wi ted locat F. Keep	and full protection to cool fiter directly introl or differential and oxygen and oxygen and oxygen and oxygen and oxygen are protection in a plastic conganics such a plastic conganics such a plastic conganics such and protection (e.g., I away from	re-exposition store into store in	gear. Ke ed surface rage cont mentering e full bund is to protect cies.  RES nup must ron may be and protect ee into a ce p up mate plastic lir away fror sonnel out ng respira  TION under pre ment is ne water. aust venti	ep contales and tainers being sewer ker gear et against wear apperent eye container erial using a specific series within a spill. So farea, tory protes exessure.	iners coo to protect ecause o s, drains including t potentia  popropriate ed for clea ewear. U for later g non-sp another Stop spi ection as  Handle a . Use ch	e Personal de Pers	f large sign-combal. Do rimaterials er. away froase if it ons warring goggles heat and	spills.  pustik not u ls (e.s) om s t can rant.  ncturi s if e
	Spills:  Work & Hygiene Practices:  Storage & Handling:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous compared by the second second by the second	reathing apparater the fire is fire the fire is fire upwin tool-over. Prevent supply, or a roved positive prombustion or defended in the fire is the fire in a cool, or over the fire in a cool, or over the fire is promptly.	atus (pressure-tout. Use waited. Avoid spraent runoff from any natural water spraent runoff from a pressure self-control of the composition of the	demand) ter spray aying waf m fire co erway. I products a  RELEA  duals involuted involutes a  quipme oak up the to soak ace into a s (e.g., or a and kee protective  ORAG  ng this p o addition sidues wi ted locat F. Keep keep cap	and full protectly ntrol or differential full protection of the control of the co	re-exposition store into store in	gear. Ke ed surface rage cont mentering e full bund is to protect cies.  RES nup must ron may be and protect pe into a ce pup mate pustic lir away fror sonnel out ng respira  TION under pre ment is ne water. aust ventitible substing n use.	ep contales and tainers being sewer ker gear et against wear appetent exterior and tainers being sewer to against wear appetent exterior and tainers within a spill. So of area, tory protest execusary lation, faitances. F	iners coo to protect ecause o s, drains including t potentia  popropriate ed for clea ewear. U g non-sp another Stop spi ection as  Handle a . Use ch	e Personal de Pers	f large sign-combal. Do rimaterials er. away froase if it ons warring goggles heat and	spills.  pustik not u ls (e.s) om s t can rant.  ncturi s if e
1 2 3	Spills:  Work & Hygiene Practices:  Storage & Handling:  Special Precautions:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous compared by the second second by the second	reathing apparater the fire is fire the fire is fire upwin tool-over. Prevent supply, or a roved positive prombustion or defended in the fire is the fire in a cool, or or in a cool, or or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is the fire in a cool, or over the fire is t	atus (pressure-tout. Use waited. Avoid sprayer trunoff from the pressure self-core composition properties are protective to or leak, individually in the protective te or sand to see successive to sand to see successive to the protective te or sand to see successive to the protective te or sand to see successive the protection of t	demand) ter spray aying wat in fire co erway. If products a  RELEA duals involutes a duals involutes a equipme oak up the to soak ace into a s (e.g., or a and kee protective  ORAC  Ing this p o addition sidues wi ted locat F. Keep keep cap	and full protectly ntrol or differential full protection of the control of the co	re-exposinto sto dution from the store of th	gear. Ke ed surface rage cont mentering e full bund is to protect cies.  RES nup must ron may be and protect pe into a ce pup mate pustic lir away fror sonnel out ng respira  TION under pre ment is ne water. aust ventitible substing n use.	ep contales and tainers being sewer ker gear et against wear appetent exterior and tainers being sewer to against wear appetent exterior and tainers within a spill. So of area, tory protest execusary lation, faitances. F	iners coo to protect ecause o s, drains including t potentia  popropriate ed for clea ewear. U for later g non-sp another Stay upwin Stop spi ection as  Handle a . Use ch ns) away	e Personal de Pers	f large sign-combal. Do rimaterials er. away froesase if it ons warring goggles theat ances from p	spills.  spi
1 2 3	Spills:  Work & Hygiene Practices:  Storage & Handling:  Special Precautions:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous compared by the second second by the second	reathing apparater the fire is fire the fire is fire upwin tool-over. Prevent supply, or a roved positive prombustion or defended in the fire is the fire in a cool, or over the fire in a cool, or over the fire is promptly.	atus (pressure-tout. Use waited. Avoid sprayer trunoff from the pressure self-core composition properties are protective to or leak, individually in the protective te or sand to see successive to sand to see successive to the protective te or sand to see successive to the protective te or sand to see successive the protection of t	demand) ter spray aying waf m fire co erway. I products a  RELEA  duals involuted involutes a  quipme oak up the to soak ace into a s (e.g., or a and kee protective  ORAG  ng this p o addition sidues wi ted locat F. Keep keep cap	and full protectly ntrol or differential full protection of the control of the co	re-exposinto sto dution from the store of th	gear. Ke ed surface rage cont mentering e full bund is to protect cies.  RES nup must and protect einto a ce p up mate plastic lir away fror sonnel out ng respira  TION under pre ment is ne vater. aust venti tible subst n use.	ep contales and tainers being sewer ker gear et against wear appetent exterior and tainers being sewer to against wear appetent exterior and tainers within a spill. So of area, tory protest execusary lation, faitances. F	iners coo to protect ecause o s, drains including t potentia  popropriate ed for clea ewear. U g non-sp another Stop spi ection as  Handle a . Use ch	e Personal de Pers	f large sign-combal. Do rimaterials er. away froase if it ons warring goggles heat and	spills.  spi
1 2 3	Spills:  Work & Hygiene Practices:  Storage & Handling:  Special Precautions:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous compared by the second second by the second	reathing apparater the fire is fire the fire is fire upwin coll-over. Prevent supply, or a roved positive prombustion or do.  6. ACCIE and any spill plastic or rubble. Wear approprious as vermiculity material such a ms, shovels, duer Keep incompilisolate immedianimal risk. Wear appropriately and the collection of the	atus (pressure-tout. Use waited. Avoid sprayer trunoff from the pressure self-core composition properties are protective to or leak, individually in the protective te or sand to see successive to sand to see successive to the protective te or sand to see successive to the protective te or sand to see successive the protection of t	demand) ter spray aying wat in fire co erway. If products a  RELEA duals involutes a duals involutes a equipme oak up the to soak ace into a s (e.g., or a and kee protective  ORAC  Ing this p o addition sidues wi ted locat F. Keep keep cap	and full protectly ntrol or differential full protection of the control of the co	re-exposinto sto dution from the store of th	gear. Ke ed surface rage cont mentering e full bund is to protect cies.  RES nup must ron may be and protect pe into a ce pup mate pustic lir away fror sonnel out ng respira  TION under pre ment is ne water. aust ventitible substing n use.	ep contales and tainers being sewer ker gear et against wear appetent exterior and tainers being sewer to against wear appetent exterior and tainers within a spill. So of area, tory protest execusary lation, faitances. F	iners coo to protect ecause o s, drains including t potentia  popropriate ed for clea ewear. U for later g non-sp another Stay upwin Stop spi ection as  Handle a . Use ch ns) away	e Personal de Pers	f large sign-combal. Do rimaterials er. away froesase if it ons warring goggles theat ances from p	spills.  spi
1 1 2 3	Spills:  Work & Hygiene Practices:  Storage & Handling:  Special Precautions:  Exposure Limits: ppm (mg/m³)	Before clea Equipment. Small Spills material suc vater or a r plastic broor Large Spills or release. done with m  7  Do not eat, container(s). contact is po Use and sto sunlight. Av damage. To Clean all spi  8. EXPO  CHEMICAL NAM NA	reathing apparater the fire is fire the fire is fire upwin coll-over. Prevent supply, or a roved positive prombustion or do.  6. ACCIE aning any spill Plastic or rubbit. Wear appropriate as vermiculity material such a ms, shovels, duer Keep incomplisolate immedianimal risk. Wear appropriate immedianimal risk. Wear appropriate immedianimal risk. Wear in a cool, coold temperature of avoid unintent avoid uninte	atus (pressure-tout. Use waited. Avoid spraight. Use waited. Avoid spraight. Use waited. Avoid spraight. Use waited. Avoid spraight. Use composition popen benefit and the second of the	demand) ter spray aying waf in fire co erway. F ontained duals inv oirrator, ey equipme oak up th to soak to soak ace into a s (e.g., or a and kee protective  ORAC  ORAC  oracle protective  ORAC	and full protocool fiter directly intrological full protocool fiter directly intrological full full full full full full full fu	re-exposinto sto lution from the sto lution from the sto lution from the store into sto lution from the store into store	gear. Ke ged surface rage continue full bunds to protectives.  RES  nup must ron may be and protective into a complete into a	ep conta es and tainers be g sewer ker gear ext against  wear ap er require container errial usin her within n spill. S of area. tory prote  container extra within her within her within her spill. S of area. tory prote  container extra within her spill. S of area. tory prote  container extra within her within her within her spill. S of area.	iners coo to protect ecause o s, drains including t potentia  popropriate ed for clea ewear. U for later g non-sp another Stop spi ection as  Handle a . Use ch  osha  osha  stel NA	e Personan-up of disposarking i conditionant and and ill or relectional proportional proportional in the memical of the memical in the memica	f large sign-combal. Do rimaterials er. away froease if it ons warranged beat and company from possible from possi	spills.  countries  co
	Spills:  Work & Hygiene Practices:  Storage & Handling:  Special Precautions:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous contained by the second by the	reathing apparater the fire is fire the fire is fire upwin coll-over. Prevent supply, or a roved positive prombustion or do.  6. ACCIE and any spill plastic or rubble. Wear approprious as vermiculity material such a ms, shovels, duer Keep incompilisolate immedianimal risk. Wear appropriately and the collection of the	atus (pressure-tout. Use waited. Avoid sprayent runoff from my natural water pressure self-corecomposition properties of the composition of th	demand) ter spray aying waf in fire co erway. If broducts a  RELEA duals invo birator, ey equipme oak up the to soak ace into a s (e.g., or a and kee protective  ORAC ing this p o addition sidues wi ited locat ing the coap becape cap  S & PE CGIH STEL NA al ventila	and full protocool fiter directly introl or differential formation of the cool fiter directly introl or differential formation of the cool	re-exposinto sto dution from the store of th	gear. Ke ed surface rage cont mentering e full bun is to protect cies.  RES nup must ron may be and protect e into a co p up mate plastic lir away from sonnel out ng respira  TION  under pre ment is ne vater.  aust venti tible subsi n use.  ROTEC  ES- PEAK NF nen this p	ep contales and tainers beg sewer ker gear et against wear appeared to the service on tainer within an spill. So of area. tory protest seven and the secondainer erial using the secondainer within an spill. So of area. tory protest secondainer within an appear to the secondainer within a sec	ppropriate ed for cleaewear. U for later g non-sp another Stay upwin Stop spi ection as  Handle a . Use ch  OSHA  STEL  NA  in use.	e Personal disposal arking in container dispo	f large sign-combal. Do rimaterials er. away froesase if it ons warra	spills.



Page 3 of 6

SDS-E-FN5S Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards SDS Revision Date: 8/3/2023 SDS Revision: 6.4 8. EXPOSURE CONTROLS & PERSONAL PROTECTION – cont'd Respiratory Protection: 8.3 No special respiratory protection is required under typical circumstances of use or handling. necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. 8.4 Eve Protection: Avoid eye contact. Protective eyewear recommended. Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling large quantities (of this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. 8.5 Hand Protection: None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. 8.6 Body Protection: No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Appearance Light green aerosol spray/mist 92 Odor Ethereal / hydrocarbon odor 9.3 Odor Threshold: NA 9.4 NA Melting Point/Freezing Point: 9.5 NA Initial Boiling Point/Boiling 9.6 NA Flashpoint: 9.7 NA Upper/Lower Flammability 9.8 NA Limits: 99 Vapor Pressure: 50 +/-5 psig @ 20 °C 9.10 Vapor Density: NA 9 11 Relative Density:  $0.852 \pm 0.012 (7.10 \pm 0.1 \text{ lb/gal})$ 9 12 Solubility Partial to complete 9.13 Partition Coefficient (log Pow): NA Autoignition Temperature 9.14 NA 9.15 **Decomposition Temperature:** NA 9.16 Viscosity NA 9.17 Other Information: 0% VOC 10. STABILITY & REACTIVITY 10.1 Stability This product is stable. 10.2 Hazardous Decomposition Oxides of carbon (CO, CO<sub>2</sub>) and sulfur (SO<sub>2</sub>). Products: 10.3 Hazardous Polymerization: Will not occur. 10.4 Conditions to Avoid Open flames, sparks and high heat

#### 10.5 Incompatible Substances: None known. 11. TOXICOLOGICAL INFORMATION Routes of Entry: Inhalation: Absorption: YES YES YES 11.1 Inaestion: Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is 11.2 available for some of the components of the product. 11.3 Acute Toxicity: See section 4.4 11.4 Chronic Toxicity See section 4.5 Suspected Carcinogen: This product does not contain any chemicals known to the State of California to cause cancer or other reproductive harm. For more information go to www.P65Warnings 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. Mutagenicity This product is not reported to produce mutagenic effects in humans. Embryotoxicity This product is not reported to produce embryotoxic effects in humans. Teratogenicity This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product See Section 4.2 11.8 Biological Exposure Indices: ΝE Physician Recommendations: 11.9 Treat symptomatically.



Page 4 of 6 SDS-E-FN5S

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards SDS Revision Date: 8/3/2023 SDS Revision: 6.4 12. ECOLOGICAL INFORMATION **Environmental Stability** 12.1 There is no specific data available for this product. 12.2 Effects on Plants & Animals: There are no specific data available for this product. 12.3 Effects on Aquatic Life: There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS Waste Disposal: 13.1 Products covered by this MSDS, in their original form, when disposed as waste, are considered non hazardous waste according to Federal RCRA regulations (40 CFR 261). Disposal should be in accordance with local, state and federal regulations. Dispose of in accordance with federal, state and local regulations. Special Considerations: 13.2 California Waste Code: 331 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1000 mL) - until 12/31/2020 UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1000 mL) 14.2 IATA (AIR): ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 500 mL) UN1950, AEROSOLS, NON-FLAMMABLE, 2.2 (LTD QTY, IP VOL ≤ 820 mL) IMDG (OCN): UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1000 mL) TDGR (Canadian GND): 14.4 UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1000 mL) or MARK PACKAGE "LIMITED QUANTITY," "LTD QTY," or "QUANT LTÉE" or "QUANTITÉ LIMITÉE" ADR/RID (EU): 14.5 UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1000 mL) SCT (MEXICO): 14.6 UN1950, AEROSOLS, 2.2 (CANTIDAD LIMITADA, IP VOL ≤ 1000 mL) 14.7 ADGR (AUS): UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1000 mL) 15. REGULATORY INFORMATION 15.1 SARA Reporting This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements: SARA TPO: 152 There are no specific Threshold Planning Quantities for the components of this product. 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory. 15.4 CERCLA Reportable Quantity: 15.5 Other Federal Requirements: This material does not contain any hazardous air pollutants. This material does not contain any material listed as a Hazardous Substance under the CWA. None of the components in this product are listed as priority pollutants under the CWA. None of the components in this product are listed as toxic pollutants under the CWA. 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. 15.7 State Regulatory Information: No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances

List (WI)

15.8

Other Requirements:

List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances

This product does not contain any chemicals known to the State of California to cause cancer, birth

defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



Page 5 of 6

SDS-E-FN5S

Prep	Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standar		lards	SDS Revision: 6.4	SDS Revision Date: 8/3/2023
	16. OTHER INFORMATION				
16.1	Other Information:	WARNING! PRESSURIZED CONATINER; No directed. Keep away from heat, hot surface, pierce or burn, even after use. Wash thorough minutes. Remove contact lenses, if present a advice/attention. Store in a well-ventilated place of 122 °F. KEEP OUT OF REACH OF CHILD	sparks, ope hly after had and easy to ce. Protect	n flames and other igniti ndling. IF IN EYES: Rin: do. Continue rinsing. I	on sources. No smoking. Do not se cautiously with water for several f eye irritation persist: Get medical
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.			
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to government regulations must be reviewed for Laboratories, Inc.'s knowledge, the information accuracy, suitability or completeness is not guar provided. The information contained herein resorted to the materials, all component properties must consult the latest edition.	or applicabi n contained aranteed an lates only to	lity to this product. To I herein is reliable and d no warranties of any ty o the specific product(s).	the best of ShipMate's & CAIG accurate as of this date; however, pe, either expressed or implied, are If this product(s) is combined with
16.4	Prepared for:	CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064-6876 Tel: +1 (800) CAIG-123 (244-4123) Fax: +1 (858) 486-8398 fax http://www.caig.com/		CAGO LABORATORIES, INC.	
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com		ShipMate* Dangerous Goods Training & Consulting	



Page 6 of 6 SDS-E-FN5S

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards

SDS Revision: 6.4

SDS Revision Date: 8/3/2023

#### **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

#### **GENERAL INFORMATION:**

CAS No.	Chemical Abstract Service Number
RTECS No.	Registry of Toxic Effects of Chemical Substances Number
EINECS No.	European Inventory of Existing Commercial Chemical Substances Number

#### **EXPOSURE LIMITS IN AIR:**

ACGIH	American Conference on Governmental Industrial Hygienists
IDLH	Immediately Dangerous to Life and Health
NOHSC	National Occupational Health and Safety Commission (Australia)
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

#### FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

#### HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

#### **HEALTH, FLAMMABILITY & REACTIVITY RATINGS:**

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



### PERSONAL PROTECTION RATINGS:

Α			
В			
С			
D			
Е			
F		H.	

G				
Н				
ı				
J			<b>9</b>	
K	9			
X	Consult y special h	our supe andling d	rvisor or irections.	SOPs for



#### OTHER STANDARD ABBREVIATIONS:

Carc	Carcinogenic
Irrit	Irritant
NA	Not Available
NR	No Results
ND	Not Determined
NE	Not Established
NF	Not Found
SCBA	Self-Contained Breathing Apparatus
Sens	Sensitization
STOT RE	Specific Target Organ Toxicity – Repeat Exposure
STOT SE	Specific Target Organ Toxicity – Single Exposure

#### NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILI	TY LIMITS IN AIR:
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

#### **HAZARD RATINGS:**

0	Minimal Hazard	FLAMMABILITY
1	Slight Hazard	\
2	Moderate Hazard	REACTIVITY
3	Severe Hazard	
4	Extreme Hazard	
ACD	Acidic	$\sim$ 2
ALK	Alkaline	
COR	Corrosive	/ <b>~~ ~~</b>
₩	Use No Water	HEALTH N
OX	Oxidizer	SPECIAL
TREFOIL	Radioactive	PRECAUTIONS

#### TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TDio	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD <sub>Io</sub> , LD <sub>Io</sub> , & LD <sub>o</sub> or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TCo, LCio, & LCo	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

#### REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System					
DOT	U.S. Department of Transportation					
TC	Transport Canada					
EPA	U.S. Environmental Protection Agency					
DSL	Canadian Domestic Substance List					
NDSL	Canadian Non-Domestic Substance List					
PSL	Canadian Priority Substances List					
TSCA	U.S. Toxic Substance Control Act					
EU	European Union (European Union Directive 67/548/EEC)					
WGK	Wassergefährdungsklassen (German Water Hazard Class)					

#### WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	<b>(A)</b>	<b>(2)</b>	(3)	$\odot$	<b>(49)</b>		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

#### CLP/GHS (1272/2008/EC) PICTOGRAMS:

			$\Diamond$			$\Leftrightarrow$		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment